

CUSTOMER FOCUSED. SOLUTION DRIVEN.



D12-2 Delivery System



STANDARD FEATURES

Frame

- Skid mounted steel frame, partially encased
- Forklift slots
- Powder coat

Operating Elements

- Turning knob for adjusting maximum pressure
- Turning knob for changing speed of delivery rate (l/min/U.S. gal/min)
- On/off switch for delivery pump (grouting pump)

Delivery Pumps

- 2x Double-acting, single-piston, horizontal pumps
- Each 60 gal/min and up to 1800 PSI
- Check valve operated suction and pressure valves
- Multi-User Mode:
2x 60 gal/min and 1800 PSI
- Single-User Mode:
1x 120 gal/min and 1800 PSI

Delivery Pressure

- 2x Pressure transmitter to digital indicator
- Data logging feature standard

Hydraulic

- Oil tank capacity approximately 151.42 l (40 U.S. gal)
- Oil filling and breather filter
- Oil level and temperature indication
- 2x Electric cooling fan

Diesel Drive

- Kubota Diesel Engine, Tier 4 Final, EU Stage III B 65.2 HP
- Liquid-cooled
- Tank capacity approximately 190 l (50 U.S. gal)
- Starter battery

Optional Electric Drive

Digital Screen

- Monitor flow and pressure on internal digital screen. Volume is calculated by stroke counting.*

Additional Features

- Integrated toolbox included
- Four work lights

Specifications

- Dimensions: 84W x 130L x 84H
- Weight: 8000 lbs

Optional Extras

- Spare parts sets
- Pressure hoses
- Remote controls

*Flow on display is a theoretical calculated volume by counting the strokes. Accuracy can be off by 100% (if suction line is not connected or hoses are plugged, etc., pump will continue to count!).

NOW DELIVERING TO U.S. MARKETS.

Contact Ben VanderWeide at 855.801.7453.

INTRIC
GROUTING SOLUTIONS

www.INTRICSOLUTIONS.com